

CA2 Counting Scale <CE.OIML>

General Features:

- High speed 24-bit AD for faster weighing response
- Faster weighing stability; faster zero return
- Quicker Zero key and Tare key
- Full-tare LCD display (Weight – 6digits, Unit Weight – 6 digits, Quantity – 6 digits)
- 10-preset unit weight function
- Auto calibration function and OL protection
- Weight and quantity over-limit warning
- Auto average unit weight; pre-tare function
- Kilogram(kg), pound(lb) weighing units
- Stable sampling range setting function
- Data accumulations (weight and quantity)
- Low power and charging status indication
- Built-in rechargeable battery
- Easily adjustable leveling feet for stability of the scale
- OIML approved model available for 1/3,000 display resolution
- Non-approval model available for up to 1/15,000 display resolution



Option:

* RS232

● Specification

Capacity	Accuracy	Resolution
3 kg	1 g	1/3,000
6 kg	2 g	1/3,000
15 kg	5 g	1/3,000
30 kg	10g	1/3,000
1.5 kg	0.1 g	1/15,000
3 kg	0.2 g	1/15,000
7.5kg	0.5 g	1/15,000
15 kg	1 g	1/15,000
30 kg	2 g	1/15,000
Pan Size (W x D)	290mm x 220mm	
Dimensions (W x D x H)	345 x 297 x 106mm	
Display	LCD, 6 / 6 / 6 digits, 14/14/18 mm (Height), LED backlight	
Power Supply	AC 110V/220V ±10% or DC 6V/4AH rechargeable battery	
Operating Temperature	Non-approval model: 0°C ~ 40°C (32°F ~ 104°F) Approval model: -10°C ~ 40°C (14°F ~ 104°F)	



EXCELL PRECISION CO., LTD.

6F, No.127, Lane 235, Pao-Chiao Road, Hsin Tien, New Taipei City, 231, Taiwan
 Tel: +886-2-89191000 Website: www.excell-scale.com
 Fax: +886-2-89191177 E-mail: pm-all@excell.com.tw