

CCW-RV-214W-1S-30-WP-DRF2

Dedicated range of automated, high speed, accurate weighing solutions specifically designed for handling **STICKY DRIED FRUIT**.


The RV series from Ishida represents the latest state of the art multihead weighing performance for speed, accuracy and reliability and comes with the industry's leading high performance specification as standard.

This multihead weigher range is designed specifically for weighing sticky dried fruit such as dates, prunes, apricots and dried grapes. It also includes an independently certified IP69K test rating – ideally suited to regular wash down environments.

The Ishida dried fruit weighers have been thoroughly tested to ensure Ishida customers receive the best in class solution for this challenging application.



Dimensions



Specifications	CCW-RV-214W-1S-30-WP-DRF2	
Weighing Capacity (per head)	400g	800g
Maximum Volume for Weighing (per dump)	4.5 litres	
Weighing Speed (variable dependent on specific product and target weight)	Up to 60 WPM	
Minimum Graduation	0.1g	0.2g
Touch Screen 3D Graphical Display (RCU)	12.1" Colour LCD display including printer (as standard)	
Weigh Cell	Ishida double-beam loadcell	
Vibration control on DFT and RFTs (essential for sticky products)	Pulse width modulation (precise and programmable vibration frequency control – independent from input frequency)	
Number of Presets	200	
Materials	Combination of Hex embossed 304 stainless steel and green teflon PC25301/2010F contact parts	
Machine Weight	Approx. 550kg	
Options	This dried fruit weigher model is a fixed high specification solution dedicated to the specific industry requirements (see specific model details)	
IP test rating of structure	Tested and independently certified to IP69K (see specific wash down instructions in operators manual)	
Air consumption (waterproof machines)	110 litres/min (ANR) 0.5 MPa Air hose - PT 3/8" (for dryer connection) Note: Air hose compressor must be provided by the end user	
Power consumption	0.5kW	
Standard compliance	Ce/UL/FDA/USDA/RoHS	

Design and specifications are subject to change without notice (please confirm dimensions at point of order).



CCW-RV-214W-1S-30-WP-DRF2



RV DRIED FRUIT 2

Features and benefits



Part of a dedicated range of automated, high speed, accurate weighing solutions specifically designed for handling dried fruit using Ishida's unrivalled industry experience.

No other multihead weigher supplier can match the experience and global installed base of Ishida and it is this expertise and sector-specific knowledge that has gone into the dried fruit solution.

The dried fruit solution is based on the highest performance RV series multihead weigher platform – this has then been configured for optimum performance for this sector.

Detailed analysis of historic installations, combined with Ishida's expert team of design and application specialists has resulted in the creation of this range of high performance sector solutions.

RV high performance features

- Capable of using all 14 heads in a single combination calculation = 16383 combinations (for maximum efficiency and minimum product giveaway per cycle)
- Simultaneous triple combination calculation (delivering up to 100% efficiency)
- 5 stage digital filter (rapid stable calculations)
- Pulse width modulation on individual radial feeders (precise programmable vibration control to achieve harmonic frequency per radial feeder - independent of input frequency for unrivalled product-specific in-feed control)
- Average weight control software internal calculation resolution to 0.01g (minimise giveaway every cycle)
- Anti-floor vibration with 4 load cells (remove back ground vibration noise from load cell calculation for maximum weighing accuracy and avoiding product giveaway or missed cycles)
- 12.1" remote control unit (RCU) - (large clear screen for rapid programmable control)
- RCU cover as standard (reduce risk of screen damage for long life)
- 200 different product pre-sets (flexible and ensures rapid product changeovers)
- 3D screen display with immediate screen refresh rates (clear intuitive data display to assist operator to continuously monitor and adjust machine performance)
- Ethernet connection - to data link machine performance to customers local area network and internal management systems
- Printer for hard copy read out
- USB access for alternative data capture and transfer
- All materials are FDA approved and comply with Article 16 (1) of Regulation (EC) number 1935/2004, and Article 15 of Regulation 10/2011

Model	DRIED FRUIT 2 - CCW-RV-214W-1S-30-WP-DRF2	
Max Piece Length	60mm	
Target Volume*	<1.35 litres	>3.15 litres
Top Speed*	60 WPM	10 WPM
Contact Parts Finish	Hex embossed (to promote free flow of product) with non-stick coatings and PTFE ribbed gates	
Dispersion Table	30° green teflon PC25301/2010F coated dispersion table (to promote free flow of sticky product)	
Ring Gate	Included with blue metal-detectable polyurethane fingers (controlling product infeed)	
Radial Feeder Troughs	6° inclined green teflon PC25301/2010F coated radial feeders (to promote free flow of sticky product)	
Hoppers	Double opening pool and weigh hoppers (for rapid product transfer), special ribbed PTFE gates (to stop product sticking)	
Discharge Chutes	60° discharge chute with anti-swirl fins (for increased product control)	
Timing Hopper	6 litre motor driven timing hopper with PTFE ribbed gates (to stop product sticking)	
Software	Multiple languages available, count priority, enhanced average weight control, error signal output, auto zero cleaning mode, remote diagnostics software	

*figures are based on historical application products and may vary depending on specific nature of product



ISHIDA EUROPE LIMITED

Kettles Wood Drive
Woodgate Business Park
Birmingham
B32 3DB
United Kingdom
Tel: +44 (0)121 607 7700
Fax: +44 (0)121 607 7888
info@ishidaeurope.com

ISHIDA CZECH REPUBLIC

Tel: +420 317 844 059
Fax: +420 317 844 052
info@ishidaeurope.cz

ISHIDA ROMANIA

Tel: +40 (0)21 589 73 52
Fax: +40 (0)21 310 34 22
info@ishidaeurope.ro

ISHIDA FRANCE

Tel: +33 (0)1 48 63 83 83
Fax: +33 (0)1 48 63 24 29
info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS

Tel: +7 499 272 05 36
Fax: +7 499 272 05 37
info@ishidaeurope.ru

ISHIDA GERMANY

Tel: +49 (0)791 945 160
Fax: +49 (0)791 945 1699
info@ishida.de

ISHIDA SOUTH AFRICA

Tel: +27 (0)11 976 2010
Fax: +27 (0)11 976 2012
info@ishidaeurope.com

ISHIDA MIDDLE EAST

Tel: +971 (0)4 299 1933
Fax: +971 (0)4 299 1955
ishida@ishida.ae

ISHIDA SWITZERLAND

Tel: +41 (0)41 799 7999
Fax: +41 (0)41 790 3927
info@ishida.ch

ISHIDA NETHERLANDS

Tel: +31 (0)499 39 3675
Fax: +31 (0)499 39 1887
info@ishida.nl